



HEBEI SHENG MAI CONSTRUCTION MATERIAL TECHNOLOGY CO.,LTD

Website:www.wiremeshfences.net Email:sales03@fencewiremesh.com Tel:+86-18032888759 Fax:+86-311-85030301

QUOTATION SHEET

Contact person: Sarah Zhou

Products Detail

The double-line-wire automatic wire mesh welding machine

The double-line-wire automatic wire mesh welding machine is mainly used to weld shaped wire mesh panels.

Feeding mode: the wefts are straightened, cut and then bent on a bending machine to finish an ideal radian; the wefts are straightened, cut and sequentially placed at corresponding positions of a wire placement mold frame.

Welding: The servo motor controls an automatic feeding process to finish welding, and the grids are uniform; pneumatic pressurization is adopted, and welding spots are firm; mesh openings, welding pressure and other welding parameters can be adjusted only by direct input on a touch screen.

Welding finish: meshes are automatically drawn by a stepper motor.

Technical parameters

Wire diameter	4-8mm	Rated voltage	AC380V
Weft distance	min50mm	Warp mode	Pre-shearing and pre-bending
Warp distance	100-300mm	Weft mode	Pre-shearing
Welding width	2000mm	Welding sport quantity	21
Welding speed	40times/min	Dimensions	12.5*2.5*1.9 (m)

