

HEBEI SHENG MAI CONSTRUCTION MATERIAL TECHNOLOGY CO.,LTD

Website:www.wiremshfences.net

Email:sales03@fencewiremesh.com Tel:+86-18032888759 Fax:+86-311-85030301

QUOTATION SHEET

Contact person: Sarah Zhou

Products Detail

Automatic Welded Wire Mesh(in roll) Machine

Automatic Welded Wire Mesh(in roll) Machine is provided with a thick-steel-plate frame, a vertical gearbox and an integrated clutching weft feeding mechanism, and straightens wires in an enclosed mode. Electromagnetic stepless speed regulation is adopted, and grids are firm and uniform; wires are firmly welded in a three-phase power electronic control mode, and the machine can be finely adjusted and controlled.

Model	Welding width	Aperture	Wire diameter	Speed (meshes/min)	Coiled mesh length	Dimensions (m)
DCD-1	2'-4'	1/2-1	0.65-2.0	≥ 50		
		1/3	0.65-1.2	(Radial	120-400m	1.5*2.3*1.6
		3/8-3/4	0.65-1.5	direction)		
DCD-2	2'-5'	1/2-1	0.65-2.0	≥ 50		
		1/3	0.65-1.2	(Radial	120-350m	1.6*2.5*1.6
		3/8-3/4	0.65-1.5	direction)		
DCD-3	4'-6'	3/8-3/4	0.65-1.5	≥ 50		
		1/3	0.65-1.2	(Radial	120-300m	1.7*3.0*1.8
		3/8-3/4	0.65-1.5	direction)		
DCD-4	4'-7'	1/2-1	0.65-2.0	≥50		
		1/3	0.65-1.2	(Radial	120-300m	1.8*3.5*1.9
		3/8-3/4	0.65-1.5	direction)		

The above parameters can be customized according to customer requirements.







