



HEBEI SHENG MAI CONSTRUCTION MATERIAL TECHNOLOGY CO.,LTD

Website: [www.wiremshfences.net](http://www.wiremshfences.net) Email: [sales03@fencewiremesh.com](mailto:sales03@fencewiremesh.com) Tel: +86-18032888759 Fax: +86-311-85030301

## QUOTATION SHEET

Contact person: Sarah Zhou

### Products Detail

#### Galvanized Razor Barbed Wire

Galvanized Razor barbed wire is a kind of modern security fencing materials fabricated with razor-sharp steel blade and high-tensile wire. It can be installed to achieve the result of frightening and stopping to the aggressive perimeter intruders, with piecing and cutting razor blades mounted at the top of the wall, also the special designs making climbing and touching extremely difficult. The wire and strip are galvanized or PVC coated to prevent corrosion.

**Material:** galvanized wire

**Process:** galvanized steel plate punched into certain forms then attached to the steel wire in sharp angle to form the blades.

Surface Treatment: galvanized or PVC coated

#### Features:

1. Razor barbed is a kind of modern security fencing materials fabricated with razor-sharp steel blade and high-tensile wire.
2. Visual and psychological deterrent.
3. Resistance to corrosion.
4. Low price and easy to install.
5. It can be installed to achieve the result of frightening and stopping to the aggressive perimeter intruders, with piecing and cutting razor blades mounted at the top of the wall, its special designs making climbing and touching extremely difficult.

#### Applications:

Galvanized Razor barbed wire is widely used by many countries in military field, prisons, detention houses, government buildings and other national security facilities. Recently years, barbed tape has apparently become the most popular high-class fencing wire for not only military and national security applications, but also for cottage and society fence, and other private buildings.

## Specifications of Razor Barbed Wire:

| Type   | Blade Style | Thickness | Wire Diameter | Blade Length | Blade Width | Blade Space |
|--------|-------------|-----------|---------------|--------------|-------------|-------------|
| BTO-10 |             | 0.5±0.05  | 2.5±0.1       | 10±1         | 13±1        | 26±1        |
| BTO-12 |             | 0.5±0.05  | 2.5±0.1       | 12±1         | 15±1        | 26±1        |
| BTO-18 |             | 0.5±0.05  | 2.5±0.1       | 18±1         | 15±1        | 33±1        |
| BTO-22 |             | 0.5±0.05  | 2.5±0.1       | 22±1         | 15±1        | 34±1        |
| BTO-28 |             | 0.5±0.05  | 2.5           | 28           | 15          | 45±1        |
| BTO-30 |             | 0.5±0.05  | 2.5           | 30           | 18          | 45±1        |
| CBT-60 |             | 0.6±0.05  | 2.5±0.1       | 60±2         | 32±1        | 100±2       |
| CBT-65 |             | 0.6±0.05  | 2.5±0.1       | 65±2         | 21±1        | 100±2       |

| Outside Diameter | No. of Loops | Standard Length per Coil | Type                  | Notes       |
|------------------|--------------|--------------------------|-----------------------|-------------|
| 450mm            | 33           | 7-8M                     | CBT-60.65             | Single coil |
| 500mm            | 56           | 12-13M                   | CBT-60.65             | Single coil |
| 700mm            | 56           | 13-14M                   | CBT-60.65             | Single coil |
| 960mm            | 56           | 14-15M                   | CBT-60.65             | Single coil |
| 450mm            | 56           | 8-9M (3 CLIPS)           | BTO-10.12.18.22.28.30 | Cross type  |
| 500mm            | 56           | 9-10M (3 CLIPS)          | BTO-10.12.18.22.28.30 | Cross type  |
| 600mm            | 56           | 10-11M (3 CLIPS)         | BTO-10.12.18.22.28.30 | Cross type  |
| 600mm            | 56           | 8-10M (5 CLIPS)          | BTO-10.12.18.22.28.30 | Cross type  |
| 700mm            | 56           | 10-12M (5 CLIPS)         | BTO-10.12.18.22.28.30 | Cross type  |
| 800mm            | 56           | 11-13M (5 CLIPS)         | BTO-10.12.18.22.28.30 | Cross type  |
| 900mm            | 56           | 12-14M (5 CLIPS)         | BTO-10.12.18.22.28.30 | Cross type  |
| 960mm            | 56           | 13-15M (5 CLIPS)         | BTO-10.12.18.22.28.30 | Cross type  |
| 980mm            | 56           | 14-16M (5 CLIPS)         | BTO-10.12.18.22.28.30 | Cross type  |

