



HEBEI SHENG MAI CONSTRUCTION MATERIAL TECHNOLOGY CO.,LTD

Website:www.wiremeshfences.net Email:sales03@fencewiremesh.com Tel:+86-18032888759 Fax:+86-311-85030301

## QUOTATION SHEET

Contact person: Sarah Zhou

### Products Detail

#### Razor barbed wire fence

**Razor barbed wire fencing** and razor wire concertina makes the majority of our products. Razor barbed wire fencing is usually made of galvanized steel blade or stainless steel blade. Two pieces of stainless steel razor wire or zinc-coated razor wire can be bounded together by clips to make it stronger. The spiral intersecting barbed wire presents an intersecting shape after opening with beautiful outlook and practical property.









**Material** for Razor Barbed Wire Fencing: Galvanized blade, stainless steel blade.

**Features:** Compact and rational structure, high safety factor, for the protection of prison and key project.

**Technical Note:** Razor barbed wire fencing can be made according to the actual dimension of customer; the special specification is manufactured according to the drawing.

In order to install a **razor concertina fencing** needs razor barbed wire and other items. There is a fencing example:

- Concertina Barbed Wire: 750mm Dia.
- Barbed Wire
- Fabric: 3.76/4.88mm, 3m high, mesh 50mm × 50mm coated.
- Brace Rail Pipe; 89.9mm, 4m high length coated epoxy green.
- Line post: hollow section 100 × 100 × 4 × 3000mm with base Plate and top Cover (post cap) coated.
- Double arm 50 × 50 × 5mm each 500mm long with 6 notches (epoxy angle plated).
- Tie Wire: 2.5mm/3.76 PVC Coated.
- Base Plate 300 × 300 × 6mm with Epoxy Paint Finish.
- Slats

Type	Blade Style	Thickness	Wire Diameter	Blade Length	Blade Width	Blade Space
BTO-10		0.5±0.05	2.5±0.1	10±1	13±1	26±1
BTO-12		0.5±0.05	2.5±0.1	12±1	15±1	26±1
BTO-18		0.5±0.05	2.5±0.1	18±1	15±1	33±1
BTO-22		0.5±0.05	2.5±0.1	22±1	15±1	34±1
BTO-28		0.5±0.05	2.5	28	15	45±1
BTO-30		0.5±0.05	2.5	30	18	45±1
CBT-60		0.6±0.05	2.5±0.1	60±2	32±1	100±2
CBT-65		0.6±0.05	2.5±0.1	65±2	21±1	100±2

Outside Diameter	No. of Loops	Standard Length per Coil	Type	Notes
450mm	33	7-8M	CBT-60.65	Single coil
500mm	56	12-13M	CBT-60.65	Single coil
700mm	56	13-14M	CBT-60.65	Single coil
960mm	56	14-15M	CBT-60.65	Single coil
450mm	56	8-9M (3 CLIPS)	BTO-10.12.18.22.28.30	Cross type
500mm	56	9-10M (3 CLIPS)	BTO-10.12.18.22.28.30	Cross type
600mm	56	10-11M (3 CLIPS)	BTO-10.12.18.22.28.30	Cross type
600mm	56	8-10M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
700mm	56	10-12M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
800mm	56	11-13M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
900mm	56	12-14M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
960mm	56	13-15M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
980mm	56	14-16M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type

