



HEBEI SHENG MAI CONSTRUCTION MATERIAL TECHNOLOGY CO.,LTD

Website: www.wiremeshfences.net Email: sales03@fencewiremesh.com Tel: +86-18032888759 Fax: +86-311-85030301

QUOTATION SHEET

Contact person: Sarah Zhou

Products Detail

Welded Razor Wire Mesh

Welded Razor Wire Mesh is a multi-functional, high security mesh fencing made of straight-blade netting welded together, packaging into a roll form for transport. Welded Razor Wire Mesh is used in operations to pave the field after the installation of a blade barrier. This product can protect you and your property, and ensures the safety of the protective barriers.









This Welded Razor Wire Mesh security fence product is almost impossible to climb or cut off with the standard tools, also it has a neat appearance.

Welded Razor Wire Mesh is installed in various parts of the world's airports, military bases, water substation, the border fence, oil depots, factories and so on.

The benefits of Welded Razor Wire Mesh :

- 1 it is almost impossible to climb.
- 2 high-strength steel core very difficult to cut off.
- 3 powerful security fence barriers neat appearance.
- 4 no secondary use, so he will not be stolen.
- 5 extremely simple to install, needs three to four to install molding.

Specifications of Razor Barbed Wire:

Type	Blade Style	Thickness	Wire Diameter	Blade Length	Blade Width	Blade Space
BTO-10		0.5±0.05	2.5±0.1	10±1	13±1	26±1
BTO-12		0.5±0.05	2.5±0.1	12±1	15±1	26±1
BTO-18		0.5±0.05	2.5±0.1	18±1	15±1	33±1
BTO-22		0.5±0.05	2.5±0.1	22±1	15±1	34±1
BTO-28		0.5±0.05	2.5	28	15	45±1
BTO-30		0.5±0.05	2.5	30	18	45±1
CBT-60		0.6±0.05	2.5±0.1	60±2	32±1	100±2
CBT-65		0.6±0.05	2.5±0.1	65±2	21±1	100±2

Outside Diameter	No. of Loops	Standard Length per Coil	Type	Notes
450mm	33	7-8M	CBT-60.65	Single coil
500mm	56	12-13M	CBT-60.65	Single coil
700mm	56	13-14M	CBT-60.65	Single coil
960mm	56	14-15M	CBT-60.65	Single coil
450mm	56	8-9M (3 CLIPS)	BTO-10.12.18.22.28.30	Cross type
500mm	56	9-10M (3 CLIPS)	BTO-10.12.18.22.28.30	Cross type
600mm	56	10-11M (3 CLIPS)	BTO-10.12.18.22.28.30	Cross type
600mm	56	8-10M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
700mm	56	10-12M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
800mm	56	11-13M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
900mm	56	12-14M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
960mm	56	13-15M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
980mm	56	14-16M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type

